



- NOTES:
1. ALL RESISTORS ARE 1/2 WATT, 5% UNLESS OTHERWISE SPECIFIED.
  2. ALL 1/8 AND 1/4 WATT RESISTORS ARE ±1%, 100PPM.
  3. \* DENOTES 20PPM WIRE TEMPERATURE COEFFICIENT.
  4. METER SWITCH S2 AS VIEWED FROM REAR; SEE ABOVE.
  5. ——— DENOTES VOLTAGE FEEDBACK SIGNAL.
  6. ——— DENOTES CURRENT FEEDBACK SIGNAL.
  7. TRANSFORMER SHOWN STRAPPED FOR 115 VAC OPERATION. SEE INSTRUCTION MANUAL FOR 220VAC.
  8. DC VOLTAGES WERE MEASURED UNDER THE FOLLOWING CONDITIONS:
    - A. SIMPSON MODEL 269 OR EQUIVALENT.
    - B. 115 VAC INPUT
    - C. VOLTAGES REFERENCED TO +S UNLESS OTHERWISE NOTED
    - D. VOLTAGES ARE TYPICAL, ±10% UNLESS OTHERWISE NOTED
    - E. ALL READINGS TAKEN IN CONSTANT VOLTAGE OPERATION AT MAXIMUM RATED OUTPUT WITH NO LOAD CONNECTED.

Figure 7-2. Model 6215A. Schematic Diagram